


ECCO-GRES™ MOSAICS

COVERINGSETC


STANDARD



Bimini Blue




Butternut




Carbon



Dover White




Chocolate



Havana Green




Marigold




Palm Green




Pearl



Nutmeg



Silhouette




Silken Gold


SPECIAL ORDER




Satin Rose




Silken Blue




Orchidia



Dusk Blue



Cameo



Merlot

OVERVIEW

Encounter the perfect blend of 'eco' and 'upscale' with Eco-Gres™ tiles and mosaics. ECO-GRES™ Mosaics are a Future-Friendly™ material made of through-body, unglazed porcelain. Highly sustainable, easy to install and maintain. Slip resistant, scratch resistant, stain and fade resistant. No need to seal or wax. Contains pre-consumer recycled content; may help contribute toward LEED® credits with USGBC project certification.

AVAILABLE SIZES

1" x 1" mosaics back mounted on 12" x 12" sheets.

SPECIFICATIONS

| | | | |
|--------------------------|-------------|--------------|----------------------------|
| Water Absorption | ASTM C-373 | ISO 10545-3 | >0.1% |
| Breaking Strength | | ISO 10545-4 | 800 N |
| Modulus of Rupture | ASTM C-99 | ISO 10545-4 | 110 N/mm ² |
| Abrasion Resistance | ASTM C-501 | ISO 10545-7 | max. 120 mm ³ |
| Linear Thermal Expansion | ASTM E-228 | ISO 10545-8 | 7,9 x 10 ⁻⁶ K-1 |
| Thermal Shock Resistance | ASTM C-484 | ISO 10545-9 | Conforms |
| Coefficient of Friction | ASTM C-1028 | ISO 10545-17 | Slip resistant, min. R 10 |
| Stain Resistance | | | Class 3 |
| Chemical Resistance | | ISO 10545-13 | |



* Approximate laboratory test values.
* Colors may not print accurately. Please request sample.



COVERINGSETC